

Specifications UNIDEN ATLANTIS 250-BK

- Das tragbare VHF Marine Funkgerät erlaubt freie Beweglichkeit
- Alle Kanäle: USA, Kanada und International
- Display und Tasten mit Hintergrundbeleuchtung für den Einsatz bei Tag und Nacht
- Verpassen Sie keinen Ruf durch dreifache Überwachung / programmierbaren Scan
- Wiederaufladbare NiMH Batterie mit der Kapazität einer Ni-Cd-Batterie (6 Monate Garantie)
- Einstellbare Sendeleistung: 5 Watt für maximale Reichweite und 1 Watt für maximale Batterielebensdauer
- Optional: externe Lautsprecher / Mikrofon Kombination
- NOAA Schlechtwetteralarm
- 3 Jahre Garantie
- JIS4 Wasserschutzklasse: Schutz vor Spritzwasser

- Handheld portable VHF marine radio lets you enjoy freedom and mobility
- All USA, International and Canadian marine channels
- Backlit LCD and keys for easy use, day or night
- Triple Watch/Programmable Scan means you never miss a call
- NiMH rechargeable battery with alkaline battery capability (6 month warranty)
- Full 5 watts setting for maximum range when you need it and 1 watt lower power, maximizing battery life, when you don't
- Optional speaker/microphone
- NOAA emergency weather alert
- 3 years warranty
- JIS4 waterproof rated and designed to protect against spray and splash

CHANNELS	All USA, Canada and International
WEATHER CHANNELS	10
CONTROLS	Volume & Power On/Off Knob, Squelch Knob, Ch Up/Down, Ch 16/Ch 9 or Triple Watch, 1 or 5 Watt, Keypad Lock, Push to Talk, UIC, Mem, Scan, Weather Alert, All NOAA WX Channels, SAME FIPS Channel readout, Battery Strength Indicator, Lock,
STATUS INDICATORS	W/5W, USA/INT/CAN, Triple Watch, TX, Mem, Scan, WX Alert, WX
CHANNEL DISPLAY	Backlit LCD
CONNECTORS	SMA Type (Female)
SIZE	2.5" (W) x 3.75" (H) x 1.125" (D)
SUPPLY VOLTAGE	12V DC Plug and AC Adapter (Included)
ANTENNA IMPEDANCE	50W
SPEAKER	4W 1.0W
OPERATING TEMPERATURE RANGE	-20°C to +50°C (-4°F to +122°F)
SHOCK AND VIBRATION	Meets or Exceeds EIA Standards, RS152B and RS204C
POWER SOURCE	NiMH Rechargeable Battery / 1200 mA(H) (included) 6AA Alkaline Battery Tray (Included) 6AA Alkaline Battery (Optional)
BATTERY INPUT VOLTAGE	7.2v NiMH
POWER OUTPUT	1Watt or 5Watt (Switch Selectable)
MODULATION	FM±5 KHz Deviation (FCC Designator F3E)
AUDIO DISTORTION	Less than 3% with 3 KHz Deviation with 1KHz Modulating Frequency
SIGNAL-TO-NOISE	45dB at 3 KHz
SPURIOUS SUPPRESSION	-60 dB at 1 Watt, -65 dB at 5 Watts
FREQUENCY STABILITY	±1.0 ppm, nominal
FREQUENCY RANGE	156 to 164 MHz
SENSITIVITY	0.25mV for 12 dB SINAD 0.35mV for 20 dB S/N
CIRCUIT	Dual Conversion Super Heterodyne PLL
SQUELCH	0.2mV Threshold
SPURIOUS RESPONSE	60 dB
ADJACENT CHANNEL SELECTIVITY	65 dB at ±25 KHz
AUDIO OUTPUT POWER	1.0 Watt (10% Distortion) into a 4W Load

Specifications Subject to change without notice.

Nimse Elektroniksysteme – Alter Weg 22 – 21706 Drochtersen - Germany

Telefon +49 (0) 41 43 / 999 70 – Telefax +49 (0) 41 43 / 999 777 - service@nimse.de – www.nimse.de